



Government of West Bengal
Office of the Director
Institute of Post Graduate Medical Education and Research
& SSKM Hospital
Centre of Excellence
244, AJC Bose Road, Kolkata-700020

Memo No: Inst./ 7168

Dated..16/12/2024...

Notification for Demonstration

This is to inform you that all of you in 'Column d' are selected as qualified Bidder after Technical Bid Evaluation for Physical Demonstration of different items (Column C) in the different Quotation (Column b) for Centre for liver Research, SDDL, IPGMER. Now you are requested to undergo Physical Demonstration of the below mentioned item (Column c) in front of Professor, Centre for liver Research, SDDL, IPGMER within ...28./12/2024 02:00 p.m. You are also directed to submit 'Annexure I' (attached herewith) within ..30./12/2024 02:00 p.m. to **Institute Store, IPGME&R, Kolkata**. Please note that if any bidder is not able to submit the 'Annexure I' after Physical Demonstration within stipulated date & time, will be treated as disqualified bidder.

Sl. No. (a)	Quotation No. with date (b)	Name of Item (c)	Name of Technically qualified Bidder (d)
1	Quotation notice no. Inst./6186 dated-24/10/2024	Bacterial Incubator with Shaker	ANNAPURNA SCIENTIFIC INSTRUMENTS CO. UNIVERSAL LABORATORY EQUIPMENTS INDO SCIENTIFIC & SURGICALS PVT. LTD. PARSHVNATH LAB SOLUTIONS VALENCY LAB EQUIPMENTS PVT. LTD. BIOAPPS S. M. SCIENTIFIC INSTRUMENTS PVT. LTD. OCEAN LIFE SCIENCE CORPORATION


14/12/24

Director
IPGME&R, Kolkata - 20



Demonstration of Bacterial Incubator with Shaker

Quotation notice no. Inst./6186 dated-24/10/2024

Name of Bidder	Specification as per Quotation	Demonstration	Remark
	<ul style="list-style-type: none"> • Outer Construction : MS power coated • Inner Construction : SS 304 • Sample viewing : Transparent Glass window • Inbuilt Lighting : Build in Lighting attachment with low wattage provided with External Switch on the front panel • Shaking Platform Size : For conical flask SS Platform size with 425 X 425mm • Shaking speed : 20-200 Orbital strokes per min. (without load) • Additional SS Tray : For Petri dishes and small beakers. • Temperature range : (5⁰C above ambient) to 70⁰C, Accuracy: ± 0.5⁰C. • Uniformity control : Fittes with recirculation fan in the chamber for uniformity of temperature. • Platform capacity : As per the table chart given below for tray size suitable clamps capacity. • Display Control : Microprocessor based PID control by using PT 100 Sensor • Speed Indicator : Digital Speed Indicator on the front panel • Mains Power : Works on 230 V AC single phase 50Hz. • Tray Size in mm : 425 X 425 • Inner Chamber Size in mm (LxDxH) : 500 X 500 X 500 • Outer Chamber Size in mm (LxDxH) : 550 X 520 X 520 • Heater : 650 Watts 		

Professor
Centre of Liver Disease
IPGME&R
Kolkata-20